

Flow Iron Swivels

Reliable swivels for well service applications

 **Working pressure:**
15,000 psi [103 MPa]

 **Sizes:**
2 or 3 in

Applications

Hydraulic fracturing, cementing, well testing, and flowback

How it improves wells

Flow iron swivels from Cameron deliver maximum total lifecycle cost savings, even in the oil and gas industry's most demanding applications. For all of your flow iron requirements, from high-stage-count hydraulic fracturing to cementing, well testing, and even abrasive flowback, you can count on Cameron for high reliability and low cost.

Additional information

Cameron offers two- and three-way flow iron swivels with high-strength stepped bearing races. Swivels are available in standard 2- and 3-in sizes with 1502 hammer wing unions.



Cameron 2-in three-way flow iron swivel.

Flow Iron Swivel Specifications

| Size, in | Configuration | Hammer Union | Swivels | Bore Diameter, in | Working Pressure, psi |
|----------|---------------|--------------|-----------|-------------------|-----------------------|
| 2 | S10 | 1502 | Three-way | 1.75 | 15,000 |
| 2 | S50 | 1502 | Two-way | 1.75 | 15,000 |
| 2 | S80 | 1502 | Three-way | 1.75 | 15,000 |
| 3 | S10 | 1502 | Three-way | 2.75 | 15,000 |
| 3 | S50 | 1502 | Two-way | 2.75 | 15,000 |
| 3 | S10 | 1502 | Three-way | 2.75 | 15,000 |

All specifications are subject to change without notice.